

Mobile Refill Station (MRS-4500)



The MRS-4500 provides a deployable breathing air refill station

FEATURES & BENEFITS

- The MRS-4500 is designed to fill from 1 to 4 Aqua Lung SEA-4500s at a time, The MRS-4500 is the next generation of the legacy MRSIII.
- The MRS-4500 can be refilled from the Aerial Life Support Air Compressor (LSAC).
- The MRS-4500 includes a rugged powder coated aluminum case with an easy to use fill panel. The fill panel is positioned at a comfortable work height when the lid is opened.
- The MRS-4500 case can be easily secured to a bulkhead for travel or easily rolled. Designed with recessed latches and handles.
- The MRS-4500 can also be used to fill the Aqua Lung SEA family with a working pressure of 3000 PSI (206 bar).
- Warranty: One year after purchase.

Part Number	AMTC-X0077
Inlet Pressure Rating	5500 PSI (380 bar)
Electrical Required	None
Refill Capability	1 to 4 SEA systems at a time
Fill QTY from 0-4500PSI (310 bar)	26 (13 cu in COPV cylinder) 19 (17.5 cu in COPV cylinder)
Fill QTY from 0-3000PSI (206 bar)	80 (1.5 cu ft AL cylinder) 59 (2.0 cu ft AL cylinder)
Stored Air Volume 330 cubic feet/ 9.4 cubic meters	Contains three CFCC (Carbon Fiber Composite Cylinders) at 5500 PSI
Dimensions (H,D,W in)	36" H ,14.3" D, 24" W
(H,D,W mm)	914mm H, 363mm D, 609mm W
Full Weight, lbs (kgs)	133 lbs (60.3 kgs)
Empty Weight, lbs (kgs)	110 lbs (49.8 kgs)
Fill Pressure Setting	0-4500 PSI (310 bar) Adjustable
Operating Range	0 to +113F / -18C to +45C